

UNIVERSAL BEAMS

AS/NZS 3679.1:2016 G300/G300SO/G350SO

Finish: Bare, Painted & Galvanised

Standard Lengths: 9, 10.5, 12, 13.5, 15, 16.5 & 18m.

Different standards/grades and lengths available upon request.



SIZE	MASS PER METRE	DIMENSIONS		THICKNESS	
		DEPTH	WIDTH	FLANGE	WEB
	kg/m	mm	mm	mm	mm
UB 150 x 14	14.0	150	75	7.0	5.0
UB 150 x 18	18.0	155	75	9.5	6.0
UB 180 x 16	16.1	173	90	7.0	4.5
UB 180 x 18	18.1	175	90	8.0	5.0
UB 180 x 22	22.2	175	90	8.0	5.0
UB 200 x 18	18.2	198	99	7.0	4.5
UB 200 x 22	22.3	202	133	7.0	5.0
UB 200 x 25	25.4	203	133	7.8	5.8
UB 200 x 30	29.8	207	134	9.6	6.3
UB 250 x 26	25.7	248	124	8.0	5.0
UB 250 x 31	31.4	252	146	8.6	6.1
UB 250 x 37	37.3	256	146	10.9	6.4
UB 310 x 32	32.0	298	149	8.0	5.5
UB 310 x 40	40.4	304	165	10.2	6.1
UB 310 x 46	46.2	307	166	11.8	6.7
UB 360 x 45	44.7	352	171	9.7	6.9
UB 360 x 51	50.7	356	171	11.5	7.3
UB 360 x 57	56.7	359	172	13.0	8.0
UB 410 x 54	53.7	403	178	10.9	7.6
UB 410 x 60	59.7	406	178	12.8	7.8
UB 460 x 67	67.1	454	190	12.7	8.5
UB 460 x 74	74.6	457	190	14.5	9.1
UB 460 x 82	82.1	460	191	16.0	9.9
UB 530 x 82	82.0	528	209	13.2	9.6
UB 530 x 92	92.4	533	209	15.6	10.2
UB 610 x 101	101.0	602	228	14.8	10.6
UB 610 x 113	113.0	607	228	17.3	11.2
UB 610 x 125	125.0	612	229	19.6	11.9